MIL/BA-5600/U Battery

- High performance non-rechargeable Lithium Sulphur Dioxide battery.
- Durable high impact plastic housing
- Unit contains these safety devices: fuse, TCO, diode, complete discharge device
- 100% final testing

This battery is engineered and designed for use in a world wide tactical environment, and is manufactured to meet and exceed US MIL-SPEC and ISO9000 methods and procedures. This battery meets the requirements of MIL-PRF-49471/8A with reference to MIL-STD-810 for:

Battery voltage	Capacity test	Electrolyte leakage
Mechanical and thermal shock	Vibration	Insulation resistance

For use in	AN/PSC-2 digital communication terminal
Replacement for	BA-5600/U, 6135-01-168-2944
Cell chemistry	Lithium Sulphur Dioxide
Typical capacity	7.5Ah
Nominal voltage	9 Volts
Cut off voltage	6 Volts
Nominal dimensions	186 x 40 mm
Maximum weight	363 gms
Case material	Lusterless green plastic
Operating temperature	-25°C to +55°C
Storage temperature	-30°C to +55°C
Shelf life	5 years
Disposal	Check with local regulations

MIL Power Limited.
Celtic House, 44 Ball Moor,
Buckingham. MK18 1RQ
England

MIL Power

Tel No. +44 (0) 1280 812402
Fax No. +44 (0) 1280 814169

Email sales@milpower.co.uk
Web Page. www.milpower.co.uk